



monitorpos

XP-D300H DIA

The high speed 80mm thermal receipt printer that does it all – Serial, USB, LAN and sound alarm with front output

D300H is fast, strong, well proven and most importantly reliable. If you need a competitively priced full function printer that can be used almost anywhere this is the model for you.

-) Run off a receipt in around 1/3 of a second with high speed 300mm/sec printing*. It's 50% faster than our standard model 801
-) Easy setup and long term reliability with USB/Serial / LAN interface. Big 2k buffer memory.
-) Cash drawer trigger port
-) Front output for shelf / under counter installation
-) Around 10 years life from printer head and cutter*
-) Onboard web interface for easy LAN setup
-) Optional audible alert for kitchen/ order applications
-) Barcode 2D compatible



XP-D300H USB/Serial/LAN specifications and performance data

Print method	Direct thermal, front exit	Power supply	DC24V 2.5A 60 watts
Print speed	300mm/sec	Interface	USB type B female, 9 pin Female RS232 serial, RJ45 LAN
Paper roll size	80mm, 0.06-0.08mm thickness	Memory	2048kb input buffer
Column size	512/576 dots/line (80mm)	Cash drawer port	RJ11/12 female, 24V 1.0Amp
Line spacing	3.75mm (changeable with commands)	Drivers	Windows, Linux, OPOS.
Fonts	ANK, Large font 12x24 dots, small font 9x17 dots	Auto cutter	Partial
Barcodes	UPC-A/E/ JAN/EAN13 /JAN/EAN8 CODABAR /ITF/ CODE 9/93/128	Operating temp	0-45°C, 10-80% humidity
Code page	PC347 (Standard Europe), West Europe plus others	Commands	ESC/POS compatible
Dimensions	185x140x134mm (d x w x h)	Gross Weight	1.84kg
Warranty	12 month RTB		

*at 300 receipts/day, 100mm per receipt, subject to normal usage and use of average to good quality till rolls

