



monitorpos

XP-H300L EPOS printer

The new Xprinter splashproof 80mm thermal printer with serial, USB and Lan – plus loud sound & light alert

H300L can be used in kitchens, hospitality applications or anywhere you need a great quality printer with multiple connection options. Now faster and with better water, oil and dust resistance

-)] Run off a receipt in less than half a second with high speed 300mm/sec printing*. It's 50% faster than our standard model 801.
-)] Supports logo printing top and bottom, plus it's 2D Barcode and QR code compatible.
-)] Big 2k buffer memory means no lost orders.
-)] Sound and light alert – plus reminder alerts for Kitchen / order applications, switchable.
-)] 24v Cash drawer trigger port.
-)] Around 10 years life from printer head and cutter*.
-)] Wall mount brackets and cable tidy supplied



XP-H300L with LAN, USB & Serial connections

XP-H300L USB/Serial/LAN specifications and performance data

Print method	Direct thermal, top exit	Power supply	DC24V 2.5A 60 watts
Print speed	300mm/sec	Interface	USB 'B' + 9 pin RS232 + RJ45LAN
Paper roll size	80mm, 0.06-0.08mm thickness	Memory	2048kb input buffer
Column size	512/576 dots/line (76mm)	Cash drawer port	RJ11/12 female, 24V 1.0Amp
Line spacing	3.75mm (change by commands)	Drivers	Windows, Linux, OPOS.
Fonts	ANK, Large font 12x24 dots, small font 9x17 dots	Auto cutter	Partial (optional, selectable)
Barcodes	UPC-A/E/ JAN/EAN13 /JAN/EAN8 CODABAR /ITF/ CODE 9/93/128	Operating temp	0-45°C, 10-80% humidity
Code page	PC347 (Europe), plus others	Commands	ESC/POS compatible
Dimensions	194x145x144mm (d x w x h)	Gross Weight	1.81kg
Warranty	12 month RTB		

*at 300 receipts/day, 100mm per receipt, subject to normal usage and use of average to good quality till rolls

